

LED 产品 0769-88030452



LED FLEXIBLE STRIP

LED ALUMINUM PROFILE

LED SILICON NEON FLEX LIGHT

深圳丽鸿光电有限公司

Shenzhen Easing Home Opto-Electronic .,Co Ltd.



Shenzhen Easing Home Opto-Electronic .,Co Ltd.

ADD 1: No 196, Tangtou Rd, Shiyan Street, Baoan District, Shenzhen, Guangdong, China

ADD 2: Building No.3, 2nd Baoshi Road, 2nd Tianliao Industrial Area, Gongming Street,

Guangming New District, Shenzhen City 518106, Guangdong Province, China

www.easinghome.com www.ledlits.com www.ledhomex.com

contact@easinghome.com

86-0755-27640099





YOUR SATISFICATION IS OUR REWARDING

**May I have this chance to be your reliable partner
on quality products and value-added service?**



RELIABILITY - QUALITY - EFFICIENCY

Company Profile

Based in Shenzhen, PRC. Since 2009, Shenzhen Easing Home Opt-electronics Co Ltd is passionate about lighting and technology, and has rapidly grown to be a leading supplier for LED strip, LED profile, LED linear light, LED silicon neon flex and other relative accessories to clients for full range product & service. Currently we Easinghome LED has a professional lighting design team of engineers and a number of automated production lines, our products have been sold to more than 80 countries and areas. We are continuing to develop the new energy conservation and environment protection, high efficient product for you.

Laboratory

Pressure soaking tester
Tensile testing,
Salt spray chamber,
Arm drop test
Transportation vibration testing
Integrating sphere test
Age testing

Machine

SMT machine
Soldering machine
Glue dispenser machine
Extrusion waterproof machine
Everfine integrating sphere,
Constant temperature & humidity test machine
Optical image coordinate measuring instrument
UV weathering testing machine,
IPX3-6 integrated waterproof testing machine
Salting mist spraying testing machine
Aging test stand

Production Facility




Testing to make our products

HI-POT TESTING AC3750V 60seconds	✓
10S ON/OFF TESTING 100000 times	✓
-20--50degree testing	✓
Aging testing 6000hours	✓
Temperature testing	✓
Luminosity distribution Test	✓
Integrating Sphere Test	✓




深圳丽鸿光电有限公司
Shenzhen Easing Home Opto-Electronic Co., Ltd.

Company Profile



LED Flexible Strip
1-30



LED Neon Flex
31-36



LED Aluminum Profile
37-100

LED LINEAR LIGHTING SOLUTION SUPPLIER

Customized led linear lights on power,color,length,connection, installation etc. is warmly welcome. With rich experience on aluminum profile and led strip since 2009, you will receive more flexible service and rich product design.





Features

- Flexible & cuttable led module
- Seamless light without shadows
- Adopting 3 step led
- No smell
- No yellowish
- No breakage
- Non-sticky
- No chemical reaction
- Dust free
- Up to 50000hrs

PU NEW WATERPROOF LED STRIP

The PU waterproof LED Strip is resistance to salty water, UV radiation, abrasion, dust and chemicals. This makes PU waterproof LED strip perfect for indoor and outdoor applications such as general outdoor lighting, swimming pools, and wellness areas as well as building, gardening and landscaping.






UP TO 100M SUPER-LONG



IP68/IP67/IP65 SILICONE GLUE ENCAPSULATED WATERPROOF STRIPS


With the new silicone integrated extrusion molding technique. It can be made into different waterproof ratings and extra-long length with high consistence. Ultra long, high brightness consistency of whole roll strips, no brightness drop. Each segment could be cut and reconnected. Built-in triodes constant current circuit design stable working.






Series	Model	LEDs/m	Voltage	Drawing	LEDs/cut(mm)	FPC Width (mm)	Max Length (m)	CCT/Color	Power W/m	LM/m	CRI	Dimming Options	IP process	Lumen Maintenance	Warranty (years)
	FLW-2110-24060-8	60	24V		6/100	8	5	2700 K 3000 K 4000 K 6500 K	4	292	>90	Dimmable		50,000 Hours	5
	FLW-2110-24120-8	120	24V		6/50	8	5	2700 K 3000 K 4000 K 6500 K	8	584	>90	Dimmable		50,000 Hours	5
6mm	FLW-2110-24180-6	180	24V		6/33.33	6	5	2700 K 3000 K 4000 K 6500 K	10	730	>90	Dimmable		50,000 Hours	5
High density	FLW-2110-24240-8	240	24V		6/25	8	5	2700 K 3000 K 4000 K 6500 K	14	1022	>90	Dimmable		50,000 Hours	5
High density	FLW-2110-24240	240	24V		6/25	10	5	2700 K 3000 K 4000 K 6500 K	16	1168	>90	Dimmable		50,000 Hours	5
NEW High density 4mm	FLW-2110-24280-4	280	24V		7/25	4	5	2700 K 3000 K 4000 K 6500 K	10	82	>90	Dimmable		50,000 Hours	5
High density	FLW-2110-24280	280	24V		7/25	10	5	2700 K 3000 K 4000 K 6500 K	16	1312	>90	Dimmable		50,000 Hours	5
NEW High density 4mm	FLW-2110-24300-4	300	24V		6/20	4	5	2700 K 3000 K 4000 K 6500 K	11	803	>90	Dimmable		50,000 Hours	5
High density	FLW-2110-24300-8	300	24V		6/20	8	5	2700 K 3000 K 4000 K 6500 K	18	1314	>90	Dimmable		50,000 Hours	5
High density	FLW-2110-12300	300	12V		3/10	10	5	2700 K 3000 K 4000 K 6500 K	18	1314	>90	Dimmable		50,000 Hours	5
High density	FLW-2110-24300	300	24V		6/20	10	5	2700 K 3000 K 4000 K 6500 K	18	1314	>90	Dimmable		50,000 Hours	5
NEW High density	FLW-2110-24350	350	24V		7/20	10	5	2700 K 3000 K 4000 K 6500 K	18	1476	>90	Dimmable		50,000 Hours	5
High density	FLW-2110-24700-8	700	24V		7/10	8	4	2700 K 3000 K 4000 K 6500 K	24	1968	>90	Dimmable		50,000 Hours	5
High density	FLW-2110-24700	700	24V		7/10	10	4	2700 K 3000 K 4000 K 6500 K	24	1968	>90	Dimmable		50,000 Hours	5
NEW CCT	FLW-3838-24120-CCT	120	24V		6/50	10	5	2700 K ↔ 6000 K	20	1710	>80	Dimmable		50,000 Hours	5
NEW CCT	FLW-3838-12120-CCT	120	12V		3/25	10	5	2700 K ↔ 6000 K	20	1710	>80	Dimmable		50,000 Hours	5
NEW CCT	FLW-3838-24084-CCT	84	24V		6/71.42	10	5	2700 K ↔ 6000 K	14	1221	>80	Dimmable		50,000 Hours	5
NEW CCT	FLW-3838-12060-CCT	60	12V		3/50	10	5	2700 K ↔ 6000 K	12	1109	>80	Dimmable		50,000 Hours	5
NEW CCT	FLW-3838-24060-CCT	60	24V		6/100	10	5	2700 K ↔ 6000 K	12	1109	>80	Dimmable		50,000 Hours	5
NEW RGB	FLW-3838-24120-RGB	120	24V		6/50	10	4	RGB	12	N/A	N/A	Dimmable		50,000 Hours	5
NEW WARM CCT High density	FLW-2216-24224-DTW	224	24V		14/62.5	10	4	2700 K ↔ 6000 K	18	1532	>90	Dimmable		50,000 Hours	5
NEW WARM CCT	FLW-2835-24120-DTW	120	24V		12/100	10	5	1800 K ↔ 6000 K	14.44	1470	>80 >90	Dimmable		50,000 Hours	5


Series	Model	LEDs/m	Voltage	Drawing	LEDs/cut(mm)	FPC Width (mm)	Max Length (m)	CCT/Color	Power W/m	LM/m	CRI	Dimming Options	IP process	Lumen Maintenance	Warranty (years)
	FLW-2835-12030-8	30	12V		3/100	8	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	7.2	792	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
	FLW-2835-24030-8	30	24V		5/166.67	8	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	7.2	718	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
	FLW-2835-12060-8	60	12V		3/50	8	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	12	1200	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
	FLW-2835-24060-8	60	24V		6/100	8	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	12	1220	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
	FLW-2835-24060-10	60	24V		6/100	10	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	14.4	1584	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
	FLW-2835-24084-10	84	24V		6/71.42	10	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	16.8	1848	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
5mm	FLW-2835-12120-5	120	12V		3/25	5	4	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	8	880	>80 >90	Dimmable	IP20	50,000 Hours	5
5mm	FLW-2835-24120-5	120	24V		6/50	5	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	8	880	>80 >90	Dimmable	IP20	50,000 Hours	5
	FLW-2835-12120-8	120	12V		3/25	8	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	15	1650	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
	FLW-2835-24120-8	120	24V		6/50	8	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	15	1650	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
	FLW-2835-12120	120	12V		3/25	10	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	24	2640	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
	FLW-2835-24120	120	24V		6/50	10	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	24	2640	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
Double row	FLW-2835-24144-15	144	24V		12/83.3	15	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	24	2640	>80 >90	Dimmable	IP20 IP42 IP54 IP65	50,000 Hours	5
High density	FLW-2835-24240	240	24V		6/25	10	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	24	2640	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
1 Cut	FLW-2835-24120	120	5/12/24		1/8.3	10	3	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	12	1320	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
15M	FLW-5050-24030	30	CC24V		5/166.67	10	15	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	7.2	540	>80 >90	Dimmable	IP20 IP42 IP54 IP65	50,000 Hours	5
	FLW-5050-12030	30	12V		3/100	10	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	7.2	612	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
	FLW-5050-24030	30	24V		5/166.67	10	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	7.2	540	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
	FLW-5050-12048	48	12V		3/62.5	10	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	9.6	816	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
	FLW-5050-24048	48	24V		6/125	10	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	9.6	816	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
	FLW-5050-12060	60	12V		3/50	10	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	14.4	1224	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
	FLW-5050-24060	60	24V		6/100	10	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	14.4	1224	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
	FLW-5050-24096-12	96	24V		6/62.5	12	4	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	23	1958	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
Double row	FLW-5050-24120-15	120	24V		6/50	15	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	24	2040	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5
Double row	FLW-5050-24120-20	120	24V		6/50	20	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	28.8	2448	>80 >90	Dimmable	IP20 IP42 IP54 IP65 IP67 IP68	50,000 Hours	5

Series	Model	LEDs/m	Voltage	Drawing	LEDs/cut(mm)	FPC Width (mm)	Max Length (m)	CCT/Color	Power W/m	LM/m	CRI	Dimming Options	IP process	Lumen Maintenance	Warranty (years)
Double row	FLW-3528-12240-15	240	12V		6/25	15	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	19.2	1440	>80 >90	Dimmable	IP20 IP42 IP54 IP65	50,000 Hours	5
Double row	FLW-3528-24240-15	240	24V		12/50	15	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	19.2	1440	>80 >90	Dimmable	IP20 IP42 IP54 IP65	50,000 Hours	5
	FLW-2216-12180	180	12V		3/16.67	10	5	2200K 2700K 3000K 4000K 6000K	12	852	>80 >90	Dimmable	IP20 IP42 IP54 IP65	50,000 Hours	5
	FLW-2216-24180	180	24V		6/33.33	10	5	2200K 2700K 3000K 4000K 6000K	12	852	>80 >90	Dimmable	IP20 IP42 IP54 IP65	50,000 Hours	5
High density	FLW-2216-12240	240	12V		3/12.5	10	5	2200K 2700K 3000K 4000K 6000K	16	1136	>80 >90	Dimmable	IP20 IP42 IP54 IP65	50,000 Hours	5
High density	FLW-2216-24240	240	24V		6/25	10	5	2200K 2700K 3000K 4000K 6000K	16	1136	>80 >90	Dimmable	IP20 IP42 IP54 IP65	50,000 Hours	5
High density	FLW-2216-12300	300	12V		3/10	10	5	2200K 2700K 3000K 4000K 6000K	18	1278	>80 >90	Dimmable	IP20 IP65	50,000 Hours	5
High density	FLW-2216-24300	300	24V		6/20	10	5	2200K 2700K 3000K 4000K 6000K	18	1278	>80 >90	Dimmable	IP20 IP65	50,000 Hours	5
High density	FLW-2216-24420	420	24V		6/14.28	10	3	2200K 2700K 3000K 4000K 6000K	22	1562	>80 >90	Dimmable	IP20 IP65	50,000 Hours	5
5mm	FLW-3528-12030	30	12V		3/100	5	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	2.4	180	>80 >90	Dimmable	IP20 IP65	50,000 Hours	5
	FLW-3528-12030	30	12V		3/100	8	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	2.4	180	>80 >90	Dimmable	IP20 IP42 IP54 IP65	50,000 Hours	5
	FLW-3528-24030	30	24V		5/33.33	8	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	2.4	168	>80 >90	Dimmable	IP20 IP42 IP54 IP65	50,000 Hours	5
5mm	FLW-3528-12060	60	12V		3/50	5	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	4.8	369	>80 >90	Dimmable	IP20 IP65	50,000 Hours	5
	FLW-3528-12060	60	12V		3/50	8	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	4.8	369	>80 >90	Dimmable	IP20 IP42 IP54 IP65	50,000 Hours	5
	FLW-3528-24060	60	24V		6/100	8	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	4.8	369	>80 >90	Dimmable	IP20 IP42 IP54 IP65	50,000 Hours	5
5mm	FLW-3528-12120	120	12V		3/25	5	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	9.6	731	>80 >90	Dimmable	IP20 IP65	50,000 Hours	5
5mm	FLW-3528-24120-5	120	24V		6/50	5	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	9.6	731	>80 >90	Dimmable	IP20 IP65	50,000 Hours	5
	FLW-3528-12120-8	120	12V		3/25	8	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	9.6	731	>80 >90	Dimmable	IP20 IP42 IP54 IP65	50,000 Hours	5
	FLW-3528-24120-8	120	24V		6/50	8	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	9.6	731	>80 >90	Dimmable	IP20 IP42 IP54 IP65	50,000 Hours	5
	FLW-3528-12180	180	12V		3/33.33	10	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	14.4	1091	>80 >90	Dimmable	IP20 IP42 IP54 IP65	50,000 Hours	5
	FLW-3528-24180	180	24V		6/66.67	10	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	14.4	1091	>80 >90	Dimmable	IP20 IP42 IP54 IP65	50,000 Hours	5
High density	FLW-3528-12240	240	12V		3/12.5	10	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	19.2	1396	>80 >90	Dimmable	IP20 IP42 IP54 IP65	50,000 Hours	5
High density	FLW-3528-24240	240	24V		6/25	10	5	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	19.2	1396	>80 >90	Dimmable	IP20 IP42 IP54 IP65	50,000 Hours	5

Series	Model	LEDs/m	Voltage	Drawing	LEDs/cut (mm)	FPC Width (mm)	Max Length (m)	CCT/Color	Power W/m	LM/m	CRI	Dimming Options	IP process	Lumen Maintenance	Warranty (years)
	FLW-2110-24308-CCT-8	308	24V		14/45.45	8	5		18	1314	>80 >90	Dimmable		50,000 Hours	5
	FLW-2835-24112-CCT	112	24V		14/125	10	5		22	2287	>80 >90	Dimmable		50,000 Hours	5
	FLW-2835-12120-CCT	120	12V		6/50	10	5		24	2438	>80 >90	Dimmable		50,000 Hours	5
	FLW-2835-24120-CCT	120	24V		12/100	10	5		24	2438	>80 >90	Dimmable		50,000 Hours	5
	FLW-2835-24120-CCT	120	24V		2/16.67	10	3		24	2438	>80 >90	Dimmable		50,000 Hours	5
	FLW-5050-12060-CCT	60	12V		6/100	10	5		14.4	1198	>80 >90	Dimmable		50,000 Hours	5
	FLW-5050-24060-CCT	60	24V		6/100	10	5		19.2	1568	>80 >90	Dimmable		50,000 Hours	5
	FLW-5050-24120-CCT-20	120	24V		12/100	20	5		24	2040	>80 >90	Dimmable		50,000 Hours	5
	FLW-3527-12060-CCT	60	12V		3/50	10	5		9.6	720	>80 >90	Dimmable		50,000 Hours	5
	FLW-3527-24060-CCT	60	24V		6/100	10	5		9.6	720	>80 >90	Dimmable		50,000 Hours	5
	FLW-3527-24120-CCT	120	24V		6/50	10	5		19.2	1698	>80 >90	Dimmable		50,000 Hours	5
	FLW-3014-24224-CCT	224	24V		14/62.5	10	5		16	1187	>80 >90	Dimmable		50,000 Hours	5
	FLW-2216-12240-CCT	240	12V		6/25	10	5		14	1136	>90	Dimmable		50,000 Hours	5
	FLW-2216-24240-CCT	240	24V		12/50	10	5		14	1136	>90	Dimmable		50,000 Hours	5
	FLW-2110-12240-CCT	240	12V		6/25	10	5		14.5	1257	>90	Dimmable		50,000 Hours	5
	FLW-3838-24120-CCT	120	24V		6/50	10	5		20	1710	>80	Dimmable		50,000 Hours	5
	FLW-3838-12120-CCT	120	12V		3/25	10	5		20	1710	>80	Dimmable		50,000 Hours	5
	FLW-3838-24084-CCT	84	24V		6/71.42	10	5		14	1221	>80	Dimmable		50,000 Hours	5
	FLW-3838-12060-CCT	60	12V		3/50	10	5		12	1109	>80	Dimmable		50,000 Hours	5
	FLW-3838-24060-CCT	60	24V		6/100	10	5		12	1109	>80	Dimmable		50,000 Hours	5
	FLW-2216-24224-DTW	224	24V		14/62.5	10	4		18	1532	>90	Dimmable		50,000 Hours	5
	FLW-2835-24120-DTW	120	24V		12/100	10	5		14.44	1470	>80	Dimmable		50,000 Hours	5

Series	Model	LEDs/m	Voltage	Drawing	LEDs/cut(mm)	FPC Width (mm)	Max Length (m)	CCT/Color	Power W/m	LM/m	CRI	Dimming Options	IP process	Lumen Maintenance	Warranty (years)
15M	L15FLW2835-CC060	60	24V		6/100	10	15	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	10.5	1324	>80 >90	Dimmable	IP20 IP42 IP67	50,000 Hours	5
20M	L20FLW2835-CC060	60	24V		6/100	12	20	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	8.5	1120	>80 >90	Dimmable	IP20 IP42 IP67	50,000 Hours	5
30M	L30FLW2835-CC090	90	36V		9/100	12	30	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	7.2	946	>80 >90	Dimmable	IP20 IP42 IP67	50,000 Hours	5
	FLW-2835-24112	112	24V		7/62.5	10	5	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	2186	2820	>80 >90	Dimmable	IP20 IP42 IP67	50,000 Hours	5
	FLW-2835-24120	120	24V		6/50	10	5	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	18	2856	>80 >90	Dimmable	IP20 IP42 IP67	50,000 Hours	5
160 Lm/W	FLW-2835-24128-12	128	24V		8/62.5	12	5	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	18	2920	>80 >90	Dimmable	IP20 IP42 IP67	50,000 Hours	5
160 Lm/W	FLW-2835-24128-W	128	24V		8/62.5	12	5	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	18	2920	>80 >90	Dimmable	IP20 IP42 IP67	50,000 Hours	5
15M	L15FLW5050-CC060	60	24V		6/100	10	15	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	9.6	923	>80 >90	Dimmable	IP20 IP42 IP67	50,000 Hours	5
15M	L15FLW3528-CC070	70	24V		7/100	10	15	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	5	425	>80 >90	Dimmable	IP20 IP42 IP67	50,000 Hours	5
30M	L30FLW3528-CC090	90	36V		9/100	12	30	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	7.2	540	>80 >90	Dimmable	IP20 IP42 IP67	50,000 Hours	5
30M	L30FLW2835-CC090	90	36V		9/100	12	30	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	7.2	540	>80 >90	Dimmable	IP20 IP42 IP67	50,000 Hours	5
50M	L50FLW2835-CC078	78	48V		13/16.67	12	50	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	4.5	521	>80 >90	Dimmable	IP20 IP42 IP67	50,000 Hours	5
CCT 15M	L15FLW2835-CC120-CCT	120	24V		12/100	12	15	2200 K ← 6000 K	12	1201	>80 >90	Dimmable	IP20 IP42 IP67	50,000 Hours	5
CCT 10M	L15FLW2835-CC140-CCT	140	24V		15/100	15	15	2200 K ← 6000 K	24	2832	>80 >90	Dimmable	IP20 IP42 IP67	50,000 Hours	5
RGB	FLW-5050-12030-RGB	30	12V		3/100	10	5	RGB	7.2	N/A	N/A	Dimmable	IP20 IP42 IP67	50,000 Hours	5
RGB	FLW-5050-24030-RGB	30	24V		5/166.7	10	5	RGB	7.2	N/A	N/A	Dimmable	IP20 IP42 IP67	50,000 Hours	5
RGB	FLW-5050-12048-RGB	48	12V		3/62.5	10	5	RGB	11.5	N/A	N/A	Dimmable	IP20 IP42 IP67	50,000 Hours	5
RGB	FLW-5050-24048-RGB	48	24V		6/125	10	5	RGB	11.5	N/A	N/A	Dimmable	IP20 IP42 IP67	50,000 Hours	5
RGB	FLW-5050-12060-RGB	60	12V		3/50	10	5	RGB	14.4	N/A	N/A	Dimmable	IP20 IP42 IP67	50,000 Hours	5
RGB	FLW-5050-24060-RGB	60	24V		6/100	10	5	RGB	14.4	N/A	N/A	Dimmable	IP20 IP42 IP67	50,000 Hours	5
RGB Double row	FLW-5050-24120-RGB-20	120	24V		6/50	20	5	RGB	28	N/A	N/A	Dimmable	IP20 IP42 IP67	50,000 Hours	5
RGB	FLW-5050-24096-RGB-12	96	24V		6/62.5	12	5	RGB	23.5	N/A	N/A	Dimmable	IP20 IP42 IP67	50,000 Hours	5
RGB	FLW-5050-24120-RGB-12	120	24V		6/50	12	4	RGB	24	N/A	N/A	Dimmable	IP20 IP42 IP67	50,000 Hours	5
RGB	FLW-3528-12060-RGB-8	60	12V		3/50	8	5	RGB	7.2	N/A	N/A	Dimmable	IP20 IP42 IP67	50,000 Hours	5

Series	Model	LEDs/m	Voltage	Drawing	LEDs/cut(mm)	FPC Width (mm)	Max Length (m)	CCT/Color	Power W/m	LM/m	CRI	Dimming Options	IP process	Lumen Maintenance	Warranty (years)
RGBW	FLW-5050-12060-RGBW	60	12V		3/50	12	5	RGBW	19.2	N/A	N/A	Dimmable		50,000 Hours	5
RGBW	FLW-5050-24060-RGBW	60	24V		6/100	12	5	RGBW	19.2	N/A	N/A	Dimmable		50,000 Hours	5
RGBW	FLW-5050-24072-RGBW	72	24V		6/83.33	12	5	RGBW	20	N/A	N/A	Dimmable		50,000 Hours	5
RGBW	FLW-5050-12084-RGBW	84	12V		3/35.7	12	5	RGBW	20	N/A	N/A	Dimmable		50,000 Hours	5
RGBW	FLW-5050-24084-RGBW	84	24V		6/71.4	12	5	RGBW	22	N/A	N/A	Dimmable		50,000 Hours	5
RGBW	FLW-5050-24096-RGBW	96	24V		6/62.5	12	5	RGBW	24	N/A	N/A	Dimmable		50,000 Hours	5
RGBW	FLW-5050-24120-RGBW	120	24V		6/50	12	4	RGBW	24	N/A	N/A	Dimmable		50,000 Hours	5
RGB CCT	FLW-5050-12030-RGBW-A	30	12V		3/100	12	5	RGB CCT	9.6	N/A	N/A	Dimmable		50,000 Hours	5
RGB CCT	FLW-5050-12060-RGBW-A	60	12V		3/50	12	5	RGB CCT	19.2	N/A	N/A	Dimmable		50,000 Hours	5
RGB CCT	FLW-5050-24060-RGBW-A	60	24V		6/100	12	5	RGB CCT	19.2	N/A	N/A	Dimmable		50,000 Hours	5
RGB CCT	FLW-5050-24072-RGBW-A	72	24V		12/166.67	16	5	RGB CCT	17.2	N/A	N/A	Dimmable		50,000 Hours	5
RGBW	FLW-5050-24072-RGBW	72	24V		12/166.67	12	5	RGBW	17.2	N/A	N/A	Dimmable		50,000 Hours	5
RGBW	FLW-5050-12060-RGBW	60	12V		6/100	10	5	RGBW	14.4	N/A	N/A	Dimmable		50,000 Hours	5
RGBW	FLW-5050-24060-RGBW	60	24V		10/166.67	10	5	RGBW	14.4	N/A	N/A	Dimmable		50,000 Hours	5
S	FLW-2835-12060-S	60	12V		3/50	8.5	4	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	8	880	>80 >90	Dimmable		50,000 Hours	5
S	FLW-2835-24060-S	60	24V		6/100	8.5	4	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	8	880	>80 >90	Dimmable		50,000 Hours	5
S	FLW-5050-12048-RGB-S	48	12V		3/62.5	12	5	RGB	7	N/A	N/A	Dimmable		50,000 Hours	5
S	FLW-2835-24048-S	48	12V		3/62.5	12	4	1800K 2200K 2700K 3000K 3500K 4000K 5000K 6000K	8	680	>80 >90	Dimmable		50,000 Hours	5


Series	Model	LEDs/m	Voltage	Drawing	LEDs/cut(mm)	FPC Width (mm)	Max Length (m)	CCT/Color	Power W/m	LM/m	CRI	Dimming Options	IP process	Lumen Maintenance	Warranty (years)
190 Lm/y	FLW-2835-CC24064	64	24V		8/125	10	5	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	9.6	1564	>80 >90	Dimmable		50,000 Hours	5
160 Lm/y	FLW-2835-24064	64	24V		8/125	10	4	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	9.6	1564	>80 >90	Dimmable		50,000 Hours	5
190 Lm/y	FLW-2835-CC24080	80	24V		8/100	10	5	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	12	1972	>80 >90	Dimmable		50,000 Hours	5
160 Lm/y	FLW-2835-24080	80	24V		8/100	10	4	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	12	1972	>80 >90	Dimmable		50,000 Hours	5
190 Lm/y	FLW-2835-CC24128	128	24V		8/62.5	12	5	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	18	2917	>80 >90	Dimmable		50,000 Hours	5
160 Lm/y	FLW-2835-2424128	128	24V		8/62.5	10	4	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	18	2917	>80 >90	Dimmable		50,000 Hours	5
190 Lm/y	FLW-2835-CC24160	160	24V		8/50	12	5	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	21	3085	>80 >90	Dimmable		50,000 Hours	5
160 Lm/y	FLW-2835-24160	160	24V		8/50	10	4	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	21	3085	>80 >90	Dimmable		50,000 Hours	5
210 Lm/y	FLW-2835-24180	180	24V		9/50	10	4	1800 K 2200 K 2700 K 3000 K 3500 K 4000 K 5000 K 6000 K	24	3297	>80 >90	Dimmable		50,000 Hours	5
Side emitting	FLW-3014-12060-5	60	12V		3/50	5	5	2700 K 3000 K 4000 K 6000 K	6	486	>80 >90	Dimmable		50,000 Hours	5
Side emitting	FLW-3014-12120-5	120	12V		3/25	5	4	2700 K 3000 K 4000 K 6000 K	12	972	>80 >90	Dimmable		50,000 Hours	5
Side emitting	FLW-3014-12060-8	60	12V		3/50	8	5	2700 K 3000 K 4000 K 6000 K	6	486	>80 >90	Dimmable		50,000 Hours	5
Side emitting	FLW-3014-24060-8	60	24V		6/100	8	5	2700 K 3000 K 4000 K 6000 K	6	487	>80 >90	Dimmable		50,000 Hours	5
Side emitting	FLW-3014-24084	84	24V		6/71.4	10	5	2700 K 3000 K 4000 K 6000 K	8.4	680	>80 >90	Dimmable		50,000 Hours	5
Side emitting	FLW-3014-12120-8	120	12V		3/25	8	4	2700 K 3000 K 4000 K 6000 K	12	972	>80 >90	Dimmable		50,000 Hours	5
Side emitting	FLW-3014-24120-8	120	24V		6/50	8	5	2700 K 3000 K 4000 K 6000 K	12	996	>80 >90	Dimmable		50,000 Hours	5
Side emitting	FLW-3014-24156-8	156	24V		6/38.5	8	5	2700 K 3000 K 4000 K 6000 K	15.6	1310	>80 >90	Dimmable		50,000 Hours	5
Side emitting	FLW-3014-24156	156	24V		6/38.5	10	5	2700 K 3000 K 4000 K 6000 K	15.6	1321	>80 >90	Dimmable		50,000 Hours	5
Side emitting	RGB FLW-020-24060-RGB	60	24V		3/50	10	4	2700 K 3000 K 4000 K 6000 K	15.6	N/A	>80 >90	Dimmable		50,000 Hours	5
Side emitting	CCT FLW-3014-12120-CCT-8	60	24V		6/50	8	4	2700 K 3000 K 4000 K 6000 K	12	996	>80 >90	Dimmable		50,000 Hours	5
Side emitting	CCT FLW-3014-12240-CCT	60	24V		6/25	10	4	2700 K 3000 K 4000 K 6000 K	18	1381	>80 >90	Dimmable		50,000 Hours	5



SMD 2216
224LEDs/m CCT Dim to WARM



Model:FLW-2216-24224-DTW



Color temperature	1800K	2000K	2500K	2700K	3000K
Lumen/m	79LM	220LM	305LM	492LM	786LM
SMD Type	2216				
Input voltage	DC24V				
Power/m	18W				
LEDs/m	224				
CRI(Ra)	90				
PCB Width	10mm				
Cutttable length	62.5mm				
Working temperature	-25°C ~45°C				
Beam angle	120°				

Product Feature

This new developed dim-to-warm LED technology with an intelligent circuit, we call it DTW LED strip that automatically changes Kelvin temp from warm white 3000K to very warm white 1800K, simply by dimming the LED light through dimmable LED power supplier or any other dimmer, such as silicon controller, 0/1-10V PWM constant voltage dimmable driver. Also compatible with DC24V PWM dimmer.

Customized design is warmly welcome, we can realize it according to our customer's requirements.


Model:FLW-2835-24120-DTW




Color temperature	2000K	2500K	2700K	3000K	3500K
Lumen/m	72LM	226LM	395LM	574LM	1470LM
SMD Type	2835				
Power/m	14.4W				
Input voltage	DC24V				
LEDs/m	120				




CCT Curve



Schematic diagram



Installation Diagram






High density

SMD 2110 700LEDs/m

Model:FLW-2110-24700



Color temperature	2700K	3000K	4000K	6000K
Lumen/m	1896LM	1934LM	2136LM	1992LM

SMD Type	2110
Input voltage	DC24V
Power/m	24W
LEDs/m	700
CRI(Ra)	90
PCB Width	10mm
Cutable length	10mm
Working temperature	-25°C ~ 45°C
Beam angle	120°




Product Feature

This new generation slim 2110 LED with only size L 2.1mm*W1.1mm is ideal light source for LED linear light. It won't snap easily even bending many times because of its strong soldering foot onto PCB.

- Excellent color consistency: ONE BIN ONLY
- Refond LED source
- SDCM<3
- CRI : Ra >95, R9 >60
- Flexible design: max 700LED/m
- Uniform lighting, ideal for backlight, various aluminum profiles

Customized design is warmly welcome, we can realize it according to our customer's requirements.

Model:FLW-2110-24350




Color temperature	2700K	3000K	4000K	6000K
Lumen/m	948LM	969LM	1068LM	996LM


SMD Type	2110
LEDs/m	350
Input voltage	DC24V
Power/m	12W



Voltage & Current Curve




Temperature & Current Curve




Installation Diagram

1. Regular connection



2. connection with dimmer






SMD 2110 300LEDs/m



Model:FLW-2110-24300



Color temperature	2700K	3000K	4000K	6000K
Lumen/m	948LM	978LM	1068LM	996LM
SMD Type	2110			
Input voltage	DC24V			
Power/m	12W			
LEDs/m	300			
CRI(Ra)	90			
PCB Width	10mm			
Cutable length	20mm			
Working temperature	-25°C ~ 45°C			
Beam angle	120°			

Product Feature

This new generation slim 2110 LED with only size L 2.1mm*W1.1mm is ideal light source for LED linear light. It won't snap easily even bending many times because of its strong soldering foot onto PCB.

- Excellent color consistency: ONE BIN ONLY
- Refond LED source
- SDCM<3
- CRI : Ra >95, R9 >60
- Flexible design: max 700LED/m
- Uniform lighting, ideal for backlight, various aluminum profiles

Customized design is warmly welcome, we can realize it according to our customer's requirements.


Model:FLW-2110-24240




Color temperature	2700K	3000K	4000K	6000K
Lumen/m	614LM	628LM	692LM	680LM
SMD Type	2110			
LEDs/m	240			
Input voltage	DC24V			
Power/m	9.6W			



Voltage & Current Curve




Temperature & Current Curve




Installation Diagram

1. Regular connection



2. connection with dimmer






CCT

SMD 3838 120LEDs/m CCT



Model:FLW-3838-24120-CCT



Color temperature	● WW	● CW	● WW+CW
Lumen/m	892LM	860LM	1710LM

SMD Type	3838
Input voltage	DC24V
Power/m	20W
LEDs/m	120
CRI(Ra)	80
PCB Width	10mm
Cuttable length	50mm
Working temperature	-25°C ~ 45°C
Beam angle	120°

Product Feature

3838SMD CCT LED Component which is dual chips in one LED has smaller size of 4.1*3.8*1.1mm. the super brightness has given perfect performance on LED linear light.

- More flexibility: max 120LED -180LED for single row LED strip.
- High output Lumen: 40-50lm per LED, IF=60mA.
- 3838SMD RGB full color is coming soon.

Customized design is warmly welcome, we can realize it according to our customer's requirements.

Model:FLW-3838-12060-CCT




Color temperature	● WW	● CW	● WW+CW
Lumen/m	447LM	432LM	858LM


SMD Type	3838
LEDs/m	60
Input voltage	DC12V
Power/m	12W




Voltage & Current Curve



Temperature & Current Curve



Installation Diagram






210
lm/w

SMD 2835 180LEDs/m
High Efficiency Constant Current Series



Model:FLW-2835-24180



Color temperature	2700K	3000K	4000K	6000K
Lumen/m	948LM	978LM	1068LM	996LM


SMD Type	2835
Input voltage	DC24V
Power/m	20W
LEDs/m	180
CRI(Ra)	80
PCB Width	10mm
Cutable length	50mm
Working temperature	-25°C ~ 45°C
Beam angle	120°

Product Feature

- High efficiency upto 210lm/w
- Max lumen 4000lm/meter
- Ra > 80, Ra 90 optional
- Constant Voltage, Constant Current 24V

Customized design is warmly welcome,
we can realize it according to our customer's
requirements.

Model:FLW-2835-24160




Color temperature	2700K	3000K	4000K	6000K
Lumen/m	3423LM	3456LM	3540LM	3468LM

SMD Type	2835
LEDs/m	160
Input voltage	DC/CC24V
Power/m	21W



Model:FLW-2835-24128



Color temperature	2700K	3000K	4000K	6000K
Lumen/m	2934LM	3956LM	3024LM	2980LM

SMD Type	2835
LEDs/m	128
Input voltage	DC/CC24V
Power/m	18W



Model:FLW-2835-24080



Color temperature	2700K	3000K	4000K	6000K
Lumen/m	1972LM	1989LM	2023LM	1997LM

SMD Type	2835
LEDs/m	80
Input voltage	DC/CC24V
Power/m	12W



Model:FLW-2835-24064




Color temperature	2700K	3000K	4000K	6000K
Lumen/m	1572LM	1580LM	1620LM	1589LM

SMD Type	2835
LEDs/m	64
Input voltage	DC/CC24V
Power/m	9.6W




CONNECTION INSTRUCTION


1. Regular connection




2. connection with dimmer




3. connection with CCT controller




4. DMX Connection



5. connection with RGB controller




6. Wiring diagram for DMX512 output




The Neon Lights 霓虹灯系列


Series	Sideview
Model	AP 0410
Size(mm)	4*10
FPC Width(mm)	6
LEDs/m	180
Power W/m	8
CCT/Color	2700K 3000K 4000K 5000K R G B
CRI(Ra)	>80 >90
IP process	IP65/IP67
Min bendin gradius(mm)	>30mm
Material	Silicon (UL,SGS)




Series	Sideview
Model	AP 0612
Size(mm)	6*12
FPC Width(mm)	8
LEDs/m	120
Power W/m	12
CCT/Color	2700K 3000K 4000K 5000K R G B
CRI(Ra)	>80 >90
IP process	IP65/IP67
Min bending radius(mm)	>30mm
Material	Silicon (UL,SGS)




Series	Sideview
Model	AP 1018
Size(mm)	10*18
FPC Width(mm)	10
LEDs/m	60
Power W/m	14.4
CCT/Color	2700K 3000K 4000K 5000K R G B RGB CCT
CRI(Ra)	>80 >90
IP process	IP65/IP67
Min bending radius(mm)	>60mm
Material	Silicon (UL,SGS)




Series	Sideview
Model	AP 302
Size(mm)	12*20
FPC Width(mm)	10
LEDs/m	60
Power W/m	14.4
CCT/Color	2700K 3000K 4000K 5000K R G B RGB CCT
CRI(Ra)	>80 >90
IP process	IP65/IP67
Min bending radius(mm)	>60mm
Material	Silicon (UL,SGS)




Series	Topview
Model	AP 1010
Size(mm)	10*10
FPC Width(mm)	6
LEDs/m	180
Power W/m	8
CCT/Color	
CRI(Ra)	>80 >90
IP process	IP65/IP67
Min bending radius(mm)	>30mm
Material	Silicon (UL,SGS)




Series	Topview
Model	APD13
Size(mm)	13*13
FPC Width(mm)	6
LEDs/m	180
Power W/m	8
CCT/Color	
CRI(Ra)	>80 >90
IP process	IP65/IP67
Min bending radius(mm)	>30mm
Material	Silicon (UL,SGS)




Series	Topview
Model	AP 1212
Size(mm)	12*12
FPC Width(mm)	8
LEDs/m	120
Power W/m	12
CCT/Color	
CRI(Ra)	>80 >90
IP process	IP65/IP67
Min bending radius(mm)	>30mm
Material	Silicon (UL,SGS)




Series	Topview
Model	APR 13
Size(mm)	13*13
FPC Width(mm)	8
LEDs/m	180
Power W/m	8
CCT/Color	
CRI(Ra)	>80 >90
IP process	IP65/IP67
Min bending radius(mm)	>30mm
Material	Silicon (UL,SGS)




Series	Topview
Model	AP 1616
Size(mm)	16*16
FPC Width(mm)	10
LEDs/m	120
Power W/m	15
CCT/Color	
CRI(Ra)	>80 >90
IP process	IP65/IP67
Min bending radius(mm)	>60mm
Material	Silicon (UL,SGS)




Series	Sideview
Model	AP 0817
Size(mm)	8*17
FPC Width(mm)	8
LEDs/m	120
Power W/m	12
CCT/Color	
CRI(Ra)	>80 >90
IP process	IP65/IP67
Min bending radius(mm)	>30mm
Material	Silicon (UL,SGS)



Series	Topview
Model	AP 2014
Size(mm)	20*14
FPC Width(mm)	12
LEDs/m	120
Power W/m	18
CCT/Color	
CRI(Ra)	>80 >90
IP process	IP65/IP67
Min bending radius(mm)	>60mm
Material	Silicon (UL,SGS)



Series	Sideview
Model	AP 1226
Size(mm)	12*26
FPC Width(mm)	12
LEDs/m	60
Power W/m	15
CCT/Color	
CRI(Ra)	>80 >90
IP process	IP65/IP67
Min bending radius(mm)	>30mm
Material	Silicon (UL,SGS)



LED SILICON NEON FLEX

High luminous efficiency, unique optical light distribution structure, uniform and soft lighting, dot-free and no shadow


High light transmittance, food-grade environmental silicone material, with good flexibility and stylish appearance, exquisite and unique

Ip67, with resistances to saline solutions, acids & alkalis, corrosive gases, fire and UV


CE, RoHs, Reach certification

Ta: -20~45°C; Tc: 0°C ~ 60°C


Series	Topview
Model	NE 0508
Size(mm)	5*8
FPC Width(mm)	6
LEDs/m	120
Power W/m	7
CCT/Color	 
CRI(Ra)	>80 >90
IP process	IP65/IP67
Min bending radius(mm)	>30mm
Material	Silicon (UL,SGS)




Series	Topview
Model	NE 1515
Size(mm)	15*15
FPC Width(mm)	10
LEDs/m	120
Power W/m	15
CCT/Color	 
CRI(Ra)	>80 >90
IP process	IP65/IP67
Min bending radius(mm)	>30mm
Material	Silicon (UL,SGS)



Series	Sideview
Model	NE1515-S
Size(mm)	15*15
FPC Width(mm)	10
LEDs/m	120
Power W/m	12
CCT/Color	 
CRI(Ra)	>80 >90
IP process	IP65/IP67
Min bending radius(mm)	>30mm
Material	Silicon (UL,SGS)



Series	Topview
Model	AP 1616B
Size(mm)	16*16
FPC Width(mm)	10
LEDs/m	120
Power W/m	15
CCT/Color	 
CRI(Ra)	>80 >90
IP process	IP65/IP67
Min bending radius(mm)	>30mm
Material	Silicon (UL,SGS)




LED ALUMINUM PROFILE LED LINEAR LIGHTING

AL6063-T5 aluminum profile with high-quality surface treatment and three optional colors of black, white and silver.


High light transmission diffuser makes dots free LED linear lighting. Customized size, structure, length and color is warmly welcome.

Support 0~10V, Bluetooth dimming.

1. Mini LED Profile




2. LED Profile for Auxiliary Lighting




2.LED Profile for Auxiliary Lighting




3.Waterproof LED Profile







4. Inground LED Profile




5. LED Profile for Wardrobe and Cabinet Light




6. LED Profile for Dry-wall




7. LED Profile for Tube Light




8. LED Profile for Step Light




9. LED Profile for Skirting Board




10. LED Profile For Up & Down Lighting




11. LED Profile for Corner





12. Driver-In LED Profile for Main Lighting






13. Big Power LED Profile for Main Lighting




14. LED Profile for Wall & Ceiling Lighting







LED Profile ALP001



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	12W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	PC/PMMA:Opal, Semi Clear, Clear	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	



LED Profile ALP002



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	12W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	PC/PMMA:Opal, Semi Clear, Clear	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	Plastic 90°, 180° jointer	

LED Profile ALP002-RL



Technical Data


Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	12W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed, Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	PC/PMMA:Opal, Semi Clear, Clear	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	




LED Profile ALP003

Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	60LED/m	
Power	15W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	PC/PMMA:Opal, Semi Clear, Clear	
End Caps	Metal	
Mounting Clips	SS	
Hanging Ropes	N/A	
Connectors	N/A	




LED Profile ALP005



Technical Data

Length	1m-3m, customized length	
Max Strip Width	10mm	
Suggested LED Strip	120LED/m	
Power	12W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	PC/PMMA:Opal, Semi Clear, Clear	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	

LED Profile ALP006






Technical Data

Length	1m-3m, customized length	
Max Strip Width	10mm	
Suggested LED Strip	120LED/m	
Power	12W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	PC/PMMA:Opal, Semi Clear, Clear	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile ALP004

Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	60LED/m	
Power	15W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed, Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	Plastic 90°, 180° jointer	



LED Profile ALP007




Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	14W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	PC/PMMA:Opal, Semi Clear, Clear	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	



LED Profile ALP025



Technical Data

Length	1m-3m, customized length	
Max Strip Width	8mm	
Suggested LED Strip	120LED/m	
Power	8W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	PVC	
Diffuser	N/A	
End Caps	Silicone	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	

LED Profile ALP026



Technical Data

Length	1m-3m, customized length	
Max Strip Width	6mm	
Suggested LED Strip	120LED/m	
Power	6W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	PVC	
Diffuser	N/A	
End Caps	Silicone	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	

LED Profile APY1101




Technical Data

Length	1m-3m, customized length	
Max Strip Width	10mm	
Suggested LED Strip	120LED/m	
Power	15W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	

LED Profile ALP015-R

Technical Data


Length	1m-3m, customized length	
Max Strip Width	20mm	
Suggested LED Strip	60LED/m	
Power	20W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	




LED Profile ALP016-R

Technical Data

Length	1m-3m, customized length	
Max Strip Width	20mm	
Suggested LED Strip	60LED/m	
Power	20W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	Plastic 90°, 180° jointer	




LED Profile ALP013



Technical Data

Length	1m-3m, customized length	
Max Strip Width	18mm	
Suggested LED Strip	120LED/m	
Power	15W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	

LED Profile ALP014



Technical Data

Length	1m-3m, customized length	
Max Strip Width	18mm	
Suggested LED Strip	120LED/m	
Power	15W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed, Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	




LED Profile ALP010




Technical Data

Length	1m-3m, customized length	
Max Strip Width	16mm	
Suggested LED Strip	120LED/m	
Power	15W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	N/A	




LED Profile ALP027



Technical Data

Length	1m-3m, customized length	
Max Strip Width	16mm	
Suggested LED Strip	60LED/m	
Power	18W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	







LED Profile ALP039

Technical Data


Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	15W/m	
CRI	Ra >80, Ra >90, Ra >95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	PC/PMMA: Opal, Semi Clear, Clear	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	



LED Profile ALP032

Technical Data


Length	1m-3m, customized length	
Max Strip Width	16-20mm	
Suggested LED Strip	60LED/m	
Power	18W/m	
CRI	Ra >80, Ra >90, Ra >95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	



LED Profile ALP040

Technical Data


Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	18W/m	
CRI	Ra >80, Ra >90, Ra >95	
Installation	Recessed, Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	PC/PMMA: Opal, Semi Clear, Clear	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	



LED Profile ALP031


Technical Data

Length	1m-3m, customized length	
Max Strip Width	18mm	
Suggested LED Strip	60LED/m	
Power	18W/m	
CRI	Ra >80, Ra >90, Ra >95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	






LED Profile ALP008



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	18W/m	
CRI	Ra >80, Ra >90, Ra >95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	


LED Profile APY1106



Technical Data

Length	1m-3m, customized length	
Max Strip Width	10mm	
Suggested LED Strip	120LED/m	
Power	15W/m	
CRI	Ra >80, Ra >90, Ra >95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile APR15



Technical Data

Length	1m-3m, customized length	
Max Strip Width	6mm	
Suggested LED Strip	120LED/m	
Power	6W/m	
CRI	Ra >80, Ra >90, Ra >95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	PC	
Diffuser	Opal PC	
End Caps	PC	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	

LED Profile APW15



Technical Data

Length	1m-3m, customized length	
Max Strip Width	10mm	
Suggested LED Strip	120LED/m	
Power	8W/m	
CRI	Ra >80, Ra >90, Ra >95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile APR64



Technical Data

Length	1m-3m, customized length	
Max Strip Width	30mm	
Suggested LED Strip	60LED/m	
Power	25W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	


LED Profile APR76



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	60LED/m	
Power	25W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	ABS	
Mounting Clips	N/A	
Hanging Ropes	SS Rope	
Connectors	N/A	

LED Profile APY9358



Technical Data

Length	1m-3m, customized length	
Max Strip Width	24mm	
Suggested LED Strip	120LED/m	
Power	30W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	





LED Profile APR3030/APR60B /APR100B/APR120B



Technical Data

Length	1m-3m, customized length	
Max Strip Width	20/30/55/60mm	
Suggested LED Strip	60LED/m	
Power	15/20/30/40W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC,	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	







LED Profile APY1415

Technical Data


Length	1m-3m, customized length	
Max Strip Width	8mm	
Suggested LED Strip	120LED/m	
Power	8W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed, Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	



LED Profile APY07

Technical Data

Length	1m-3m, customized length	
Max Strip Width	5.8mm	
Suggested LED Strip	120LED/m	
Power	6W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	




APY07

APY08




LED Profile ALP116



Technical Data

Length	1m-3m, customized length	
Max Strip Width	5mm	
Suggested LED Strip	120LED/m	
Power	6W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed, Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile ALP117



Technical Data

Length	1m-3m, customized length	
Max Strip Width	5mm	
Suggested LED Strip	120LED/m	
Power	6W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile APY1612



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	12W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed, Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile APY2121



Technical Data

Length	1m-3m, customized length	
Max Strip Width	16mm	
Suggested LED Strip	120LED/m	
Power	12W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile APY00



Technical Data

Length	1m-3m, customized length	
Max Strip Width	10mm	
Suggested LED Strip	120LED/m	
Power	12W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile APY16



Technical Data

Length	1m-3m, customized length	
Max Strip Width	10mm	
Suggested LED Strip	120LED/m	
Power	12W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile ALP053



Technical Data

Length	1m-3m, customized length	
Max Strip Width	30mm	
Suggested LED Strip	60LED/m	
Power	24W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	


LED Profile AP3820



Technical Data

Length	1m-3m, customized length	
Max Strip Width	16mm	
Suggested LED Strip	120LED/m	
Power	16W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PMMA	
End Caps	Metal	
Mounting Clips	N/A	
Hanging Ropes	SS Rope	
Connectors	N/A	


LED Profile ALP043



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	14W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	

LED Profile ALP044-PC




Technical Data

Length	1m-3m, customized length	
Max Strip Width	20mm	
Suggested LED Strip	120LED/m	
Power	16W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	




LED Profile ALP111-S



Technical Data

Length	1m-3m, customized length	
Max Strip Width	22mm	
Suggested LED Strip	120LED/m	
Power	16W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	


LED Profile ALP065



Technical Data

Length	1m-3m, customized length	
Max Strip Width	40mm	
Suggested LED Strip	60LED/m(2pcs)	
Power	30W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	



LED Profile ALP066



Technical Data

Length	1m-3m, customized length	
Max Strip Width	40mm	
Suggested LED Strip	60LED/m(2pcs)	
Power	30W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	


LED Profile ALP065-T



Technical Data

Length	1m-3m, customized length	
Max Strip Width	40mm	
Suggested LED Strip	60LED/m(2pcs)	
Power	30W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	


LED Profile ALP104



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	14W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	


LED Profile ALP105



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	14W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	







LED Profile ALP018-R3

Technical Data



Length	1m-3m, customized length	
Max Strip Width	24mm	
Suggested LED Strip	60LED/m	
Power	20W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	Metal 90°, 120°, 180° jointer	



LED Profile ALP17-R5

Technical Data

Length	1m-3m, customized length	
Max Strip Width	24mm	
Suggested LED Strip	60LED/m	
Power	20W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	Metal 90°, 120°, 180° jointer	




LED Profile ALP046




Technical Data


Length	1m-3m, customized length	
Max Strip Width	38mm	
Suggested LED Strip	60LED/m	
Power	28W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	Metal 90°, 120°, 180° jointer	




APY5036



ALP046-R



ALP046-RD




ALP046

LED Profile ALP045




Technical Data


Length	1m-3m, customized length	
Max Strip Width	38mm	
Suggested LED Strip	60LED/m	
Power	28W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	Metal 90°, 120°, 180° jointer	




APY6535




ALP045




ALP045-R



ALP045-RD




LED Profile ALP9035




Technical Data


Length	1m-3m, customized length	
Max Strip Width	60mm	
Suggested LED Strip	60LED/m	
Power	28W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	Metal 90°, 120°, 180° jointer	




ALP047-R1



ALP047-R1D




ALP9035




ALP9035-D

LED Profile ALP7535




Technical Data


Length	1m-3m, customized length	
Max Strip Width	60mm	
Suggested LED Strip	60LED/m	
Power	28W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	Metal 90°, 120°, 180° jointer	




ALP048-R1



ALP048-R1D




ALP7535



ALP7535-D




LED Profile APY10235



Technical Data

Length	1m-3m, customized length	
Max Strip Width	80mm	
Suggested LED Strip	60LED/m	
Power	42W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	


LED Profile APY11735



Technical Data

Length	1m-3m, customized length	
Max Strip Width	80mm	
Suggested LED Strip	60LED/m	
Power	42W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	


LED Profile ALP12335



Technical Data

Length	1m-3m, customized length	
Max Strip Width	76mm	
Suggested LED Strip	60LED/m	
Power	45W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	Metal 90°, 120°, 180° jointer	


LED Profile ALP15023



Technical Data

Length	1m-3m, customized length	
Max Strip Width	26mm	
Suggested LED Strip	120LED/m	
Power	36W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	

LED Profile APY14232




Technical Data

Length	1m-3m, customized length	
Max Strip Width	130mm	
Suggested LED Strip	60LED/m	
Power	60W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	




LED Profile ALP057



Technical Data

Length	1m-3m, customized length	
Max Strip Width	62mm	
Suggested LED Strip	60LED/m(3pcs)	
Power	32W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	


LED Profile ALP3875



Technical Data

Length	1m-3m, customized length	
Max Strip Width	27mm	
Suggested LED Strip	60LED/m	
Power	24W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	


LED Profile ALP056-D



Technical Data

Length	1m-3m, customized length	
Max Strip Width	34mm	
Suggested LED Strip	60LED/m(2pcs)	
Power	30W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	


LED Profile ALP5075-C



Technical Data

Length	1m-3m, customized length	
Max Strip Width	26mm	
Suggested LED Strip	120LED/m	
Power	28W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	Metal 90°, 120°, 180° jointer	



LED Profile ALP056



Technical Data

Length	1m-3m, customized length	
Max Strip Width	28mm	
Suggested LED Strip	60LED/m(2pcs)	
Power	30W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	


LED Profile ALP6545-C



Technical Data

Length	1m-3m, customized length	
Max Strip Width	24mm	
Suggested LED Strip	60LED/m	
Power	20W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	Metal 90°, 120°, 180° jointer	


LED Profile ALP063



Technical Data


Length	1m-3m, customized length	
Max Strip Width	26mm	
Suggested LED Strip	60LED/m	
Power	24W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	

LED Profile ALP60108



Technical Data


Length	1m-3m, customized length	
Max Strip Width	34mm	
Suggested LED Strip	60LED/m	
Power	32W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed, Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	Metal 90°, 120°, 180° jointer	



LED Profile ALP5075-R

Technical Data


Length	1m-3m,customized length	
Max Strip Width	26mm	
Suggested LED Strip	60LED/m	
Power	38W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	Metal 90°,120°,180° jointer	




LED Profile ALP6875-R

Technical Data

Length	1m-3m,customized length	
Max Strip Width	26mm	
Suggested LED Strip	60LED/m	
Power	38W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	Metal 90°,120°,180° jointer	




LED Profile ALP7575-R



Technical Data



Length	1m-3m,customized length	
Max Strip Width	40mm	
Suggested LED Strip	60LED/m	
Power	48W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	Metal 90°,120°,180° jointer	

LED Profile ALP9575-R




Technical Data

Length	1m-3m,customized length	
Max Strip Width	40mm	
Suggested LED Strip	60LED/m	
Power	48W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	Metal 90°,120°,180° jointer	





LED Profile APY10270



Technical Data

Length	1m-3m, customized length	
Max Strip Width	80mm	
Suggested LED Strip	60LED/m	
Power	48W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	N/A	
Hanging Ropes	SS Rope	
Connectors	Metal 90°, 120°, 180° jointer	



LED Profile APY5085



Technical Data

Length	1m-3m, customized length	
Max Strip Width	31mm 20mm	
Suggested LED Strip	60LED/m(2PCS)	
Power	48W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	Metal 90°, 120°, 180° jointer	


LED Profile ALP10078



Technical Data

Length	1m-3m, customized length	
Max Strip Width	68mm	
Suggested LED Strip	60LED/m	
Power	48W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	Metal 90°, 120°, 180° jointer	



LED Profile ALP6090



Technical Data

Length	1m-3m, customized length	
Max Strip Width	35mm 30mm	
Suggested LED Strip	60LED/m(2pcs)	
Power	48W/m	
CRI	Ra >80, Ra>90	
Installation	Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	Metal 90°, 120°, 180° jointer	


LED Profile ALP8585



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m(2pcs)	
Power	38W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	Metal 90°, 120°, 180° jointer	


LED Profile ALP107



Technical Data

Length	1m-3m, customized length	
Max Strip Width	16mm	
Suggested LED Strip	120LED/m	
Power	18W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	N/A	


LED Profile ALP5090



Technical Data

Length	1m-3m, customized length	
Max Strip Width	26mm	
Suggested LED Strip	60LED/m(2PCS)	
Power	48W/m	
CRI	Ra >80, Ra>90,	
Installation	Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	SS Rope	
Connectors	Metal 90°, 120°, 180° jointer	


LED Profile ALP021



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	15W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile APT37



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	12W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile APY2601



Technical Data


Length	1m-3m, customized length	
Max Strip Width	20mm	
Suggested LED Strip	120LED/m	
Power	15W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	

LED Profile APW33




Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	12W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	






LED Profile AL-D01



Technical Data

Length	1m-3m, customized length	
Max Strip Width	10-12mm	
Suggested LED Strip	120LED/m	
Power	10W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	ABS	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile AL-D12



Technical Data

Length	1m-3m, customized length	
Max Strip Width	10mm	
Suggested LED Strip	120LED/m	
Power	10W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	Metal 90°, 120°, 180° jointer	


LED Profile AL-D13



Technical Data

Length	1m-3m, customized length	
Max Strip Width	15mm	
Suggested LED Strip	72LED/m	
Power	20W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	Metal 90°, 120°, 180° jointer	


LED Profile AL-D11



Technical Data

Length	1m-3m, customized length	
Max Strip Width	20mm	
Suggested LED Strip	120LED/m	
Power	20W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	Metal 90°, 120°, 180° jointer	



LED Profile AL-D14



Technical Data

Length	1m-3m, customized length	
Max Strip Width	36-46mm	
Suggested LED Strip	120LED/m	
Power	30-40W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	Metal 90°, 120°, 180° jointer	


LED Profile AL-D07



Technical Data

Length	1m-3m, customized length	
Max Strip Width	20mm	
Suggested LED Strip	120LED/m	
Power	18W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile AL-D06



Technical Data

Length	1m-3m, customized length	
Max Strip Width	20mm	
Suggested LED Strip	120LED/m	
Power	18W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile AL-D26



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	12W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile AL-D02



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	12W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile AL-D03



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	12W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	N/A	

LED Profile AL-D25




Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	12W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	N/A	




LED Profile AL-D04



Technical Data

Length	1m-3m, customized length	
Max Strip Width	10mm	
Suggested LED Strip	120LED/m	
Power	12W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile AL-D05



Technical Data

Length	1m-3m, customized length	
Max Strip Width	10mm	
Suggested LED Strip	120LED/m	
Power	12W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC	
End Caps	Metal	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile AL-D20



Technical Data

Length	1m-3m, customized length	
Max Strip Width	20mm	
Suggested LED Strip	60LED/m	
Power	21W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	ABS	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	N/A	

LED Profile ALP3030-R



Technical Data



Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	60LED/m	
Power	22W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	Metal 90°, 120°, 180° jointer	

LED Profile AL-D57





Technical Data

Length	1m-3m, customized length	
Max Strip Width	12-52mm	
Suggested LED Strip	60LED/m	
Power	12-40W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	N/A	




LED Profile AL-D23



Technical Data

Length	1m-3m, customized length	
Max Strip Width	22mm	
Suggested LED Strip	60LED/m	
Power	36W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	Metal 90°, 120°, 180° jointer	


LED Profile AL-D34



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	20W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile AL-D50



Technical Data

Length	1m-3m, customized length	
Max Strip Width	18mm	
Suggested LED Strip	120LED/m	
Power	18W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	Metal	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile AL-D35



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	24W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	N/A	


LED Profile AL-C01



Technical Data


Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	24W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	M/A	
Hanging Ropes	N/A	
Connectors	N/A	

LED Profile AL-C03





Technical Data

Length	1m-3m, customized length	
Max Strip Width	20mm	
Suggested LED Strip	120LED/m	
Power	28W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	



LED Profile AL-C06



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	18W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	Metal 90°, 120°, 180° jointer	


LED Profile AL-C05



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	18W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	Metal 90°, 120°, 180° jointer	


LED Profile AL-D22



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	18W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	

LED Profile AL-D36



Technical Data



Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	18W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	N/A	
End Caps	Metal	
Mounting Clips	Metal	
Hanging Ropes	N/A	
Connectors	N/A	

LED Profile APT20




Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	30W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	Plastic 90°, 120°, 180° jointer	





LED Profile ALP024-R



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	18W/m	
CRI	Ra >80, Ra >90, Ra >95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	


LED Profile APT4301



Technical Data

Length	1m-3m, customized length	
Max Strip Width	10mm	
Suggested LED Strip	120LED/m	
Power	18W/m	
CRI	Ra >80, Ra >90, Ra >95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	Metal	



LED Profile AL-D29



Technical Data


Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	18W/m	
CRI	Ra >80, Ra >90, Ra >95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	

LED Profile ALP024



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	18W/m	
CRI	Ra >80, Ra >90, Ra >95	
Installation	Surface Mounted	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC, Semi Clear PC, Clear PC	
End Caps	ABS	




LED Profile APT0501




Technical Data

Length	1m-3m, customized length	
Max Strip Width	12-21mm	
Suggested LED Strip	120LED/m	
Power	10-20W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PMMA	




APT0501




APT1501

LED Profile APT0504




Technical Data


Length	1m-3m, customized length	
Max Strip Width	12-21mm	
Suggested LED Strip	120LED/m	
Power	10-20W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PMMA	



APT0504



APT1503




APT03-AL3

LED Profile APT0503



Technical Data

Length	1m-3m, customized length	
Max Strip Width	12-21mm	
Suggested LED Strip	120LED/m	
Power	10-20W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed, Suspended	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PMMA	



APT0503





APT1502





APT03-AL2

LED Profile ALP033



LED Profile ALP034




Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	24W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	ABS	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	N/A	


Technical Data

Length	1m-3m, customized length	
Max Strip Width	12mm	
Suggested LED Strip	120LED/m	
Power	24W/m	
CRI	Ra >80, Ra>90, Ra>95	
Installation	Recessed	
Product Options	Materials	Note
Aluminum Channel	AL6063-T5	
Diffuser	Opal PC	
End Caps	ABS	
Mounting Clips	N/A	
Hanging Ropes	N/A	
Connectors	N/A	




Professional LED linear lights


Multi-functional applications and connection with reflector, frosted diffuser, wall washer, reflective louver, prismatic cover and blind plate. Magic light creates infinite possibilities




LS50-2A




LS50-2B



LS30-4A



LS30-4B




LS530-4A




LS50-Wall Washer




LS30-2A



LS50-Reflective Louver



LS50-Prismatic Cover



LS30-8A

